



acting for and on behalf of Qatar Petroleum for the لفائدة وبالإنيابة عن شركة قطر للبترول  
 Sale of Petroleum Products Company Limited لبيع المنتجات البترولية المحدودة

## STANDARD SPECIFICATION QATAR LAND CRUDE OIL

These specifications are for information purposes only and shall not be binding upon the Seller. The Seller will bear no liability for delivering crude that doesn't conform to these specifications.

Test	Method	Unit	Value
API Gravity @ 60 <sup>o</sup> F	Calculated	° API	40.5 - 39.4*
Density @ 15 <sup>o</sup> C	ASTM D5002	kg/L	0.8274
Specific Gravity @ 60/60 <sup>o</sup> F	Conversion	-	0.8278
Total Sulphur	ASTM D4294	% Wt.	1.35
Mercaptan Sulphur	UOP 163	ppm wt.	220
Hydrogen Sulphide	UOP 163	ppm wt.	110
Total Acid Number	ASTM D664	mgKOH/g	0.10
Pour Point	ASTM D97	°F	< - 22
Reid Vapour Pressure	ASTM D5191	psi	5.35
Kinematic Viscosity @ 15 <sup>o</sup> C	ASTM D445	cSt	6.208
Salt Content	ASTM D3230	PTB	3.8
Wax Content	UOP 46	% Wt.	< 5
Water Content	ASTM D4006	%Vol.	0.0

\*The API may vary due to weather conditions and/or mix of different grades of crude.

